



SYGEF Plus Adaptor socket
Installation fitting with female thread NPT SDR21/PN16
High Purity clean-room product ISO Class 5 (100)

Model:

- Material: PVDF-HP
- With butt fusion spigot and taper female thread NPT
- Avoid stresses when installing and large changes in temperature
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVDF

Note:

* Please keep strictly to the GF internal installation preferences

d (mm)	DN (mm)	Thread Type	Size (inch)	PN (bar)	SDR	FM	Sensor Type
25	20	NPT	¾	16	21	BCF, IR	pH/ORP: 272X, 277X Con- ductivity: 2819-2842 Temperature: 2350 Pressure: 2450
32	25	NPT	1	16	21	BCF, IR	pH/ORP: 276X
40	32	NPT	1 ¼	16	21	BCF, IR	
50	40	NPT	1 ½	16	21	BCF, IR	pH/ORP: 3719-11
*	63	NPT	2	16	21	BCF, IR	pH/ORP: 3719-21

d (mm)	Code	SP	Weight (kg)	e (mm)	L (mm)	s (mm)	L1 (mm)
25	735 914 787	1	0.033	1.9	58	38	30
32	735 914 788	1	0.066	2.4	63	48	30
40	735 914 789	1		2.4	67	58	30
50	735 914 790	1	0.108	3.0	67	65	30
*	735 914 791	1	0.190	3.0	73	80	30

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
 info.ps@georgfischer.com Internet: <http://www.gfps.com>