



**Line strainer type 305 PVC-U**  
**Transparent body with solvent cement spigots metric**

**Model:**

- Protects valves, pumps, etc. from becoming soiled
- Easy dismantling for cleaning the screens
- **Screen perforation need be ordered separately**
- Overall length according to EN 558

d (mm)	DN (mm)	PN (bar)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
20	15	10	<b>192 305 300</b>	1	0.098	<b>192 305 349</b>	1	0.100
25	20	10	<b>192 305 350</b>	1	0.143	<b>192 305 399</b>	1	0.170
32	25	10	<b>192 305 400</b>	1	0.227	<b>192 305 449</b>	1	0.227
40	32	10	<b>192 305 450</b>	1	0.342	<b>192 305 499</b>	1	0.346
50	40	10	<b>192 305 500</b>	1	0.589	<b>192 305 549</b>	1	0.594
63	50	10	<b>192 305 550</b>	1	0.968	<b>192 305 599</b>	1	0.972
75	65	10	<b>192 305 600</b>	1	1.826	<b>192 305 649</b>	1	1.838
90	80	10	<b>192 305 650</b>	1	2.548	<b>192 305 699</b>	1	2.565

d (mm)	D (mm)	H (mm)	L (mm)	L1 (mm)	L2 (mm)	closest inch (inch)
20	43	65	124	130	28	½
25	47	76	144	150	37	¾
32	56	90	154	160	37	1
40	64	104	174	180	44	1 ¼
50	82	124	194	200	48	1 ½
63	95	148	224	230	60	2
75	106	188	284	290	74	2 ½
90	120	205	300	310	85	3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>