




Ball valve type 542 PVC-U
With cemented spigots metric

Model:

- For easy installation and removal
- Ball seat PTFE/ red lever

Option:

- Individual configuration of the valve possible
- Assembling of a valve tag possible



d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (L/min)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
16	10	3/8	16	71	161 542 041	1	0.155	161 542 051	1	0.155
20	15	1/2	16	185	161 542 042	1	0.155	161 542 052	1	0.155
25	20	3/4	16	350	161 542 043	1	0.240	161 542 053	1	0.240
32	25	1	16	700	161 542 044	1	0.351	161 542 054	1	0.351
40	32	1 1/4	16	1000	161 542 045	1	0.610	161 542 055	1	0.610
50	40	1 1/2	16	1600	161 542 046	1	0.840	161 542 056	1	0.840
63	50	2	16	3100	161 542 047	1	1.602	161 542 057	1	1.602

d (mm)	D (mm)	H (mm)	L (mm)	L1 (mm)	L2 (mm)	L5 (mm)	L6 (mm)	e (mm)
16	50	54	114	72	56	26	46	3.1
20	50	54	124	72	56	26	46	3.1
25	58	66	144	93	65	34	59	3.1
32	68	71	155	93	71	34	59	4.1
40	84	85	175	110	85	41	69	4.6
50	97	92	193	110	89	41	69	5.6
63	124	108	224	128	101	49	79	7.1

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>