


PRO-FIT elbow 90° PVC-U metric



Model:

- Outlet: A = solvent cemented socket metric
- Outlet: B = solvent cemented spigot in combination with reducing socket metric
- Direct connection from fitting to fitting allowing shortest possible overall length



d (mm)	d1 (mm)	PN (bar)	Code	SP	Weight (kg)	z (mm)	z1 (mm)	z2 (mm)	D (mm)	L (mm)	L1 (mm)
20	16	16	721 100 306	10	0.011	11	16	18	25	27	32
25	20	16	721 100 307	10	0.020	14	18	21	31	33	37
32	25	16	721 100 308	10	0.038	17	22	25	38	39	44
40	32	16	721 100 309	10	0.069	23	30	34	47	49	56
50	40	16	721 100 310	10	0.122	26	36	41	58	57	67
63	50	16	721 100 311	10	0.237	33	45	52	73	71	83

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>