



SYGEF Standard adaptor socket female NPT SDR21/PN16

Model:

- Material: PVDF
- With butt fusion spigot and taper female thread NPT
- Avoid stresses when installing and large changes in temperature
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVDF

Note:

* Please keep strictly to the GF internal installation preferences

d (mm)	Thread Type	Size (inch)	DN (mm)	PN (bar)	SDR	FM	Sensor Type
25	NPT	¾	20	16	21	BCF, IR	pH/ORP: 272X, 277X Con- ductivity: 2819-2842 Temperature: 2350 Pressure: 2450
32	NPT	1	25	16	21	BCF, IR	ph/ORP: 276X
40	NPT	1 ¼	32	16	21	BCF, IR	
50	NPT	1 ½	40	16	21	BCF, IR	pH/ORP: 3719-11
*	NPT	2	50	16	21	BCF, IR	pH/ORP: 3719-21

d (mm)	Code	SP	Weight (kg)	e (mm)	L (mm)	s (mm)	L1 (mm)
25	735 914 587	1	0.033	1.9	58	38	30
32	735 914 588	1	0.066	2.4	63	48	30
40	735 914 589	1	0.085	2.4	67	58	30
50	735 914 590	1	0.108	3.0	67	65	30
*	735 914 591	1	0.190	3.0	73	80	30

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>