



**Valve end 546 Pro and 543 Pro PVC-U (G05)  
With solvent cement spigot metric**

d (mm)	PN (bar)	Code	Weight (kg)	D (mm)	D1 (mm)	D2 (mm)	L (mm)	L1 (mm)	z (mm)
16	16	<b>161 490 701</b>	0.011	38	10	16	29	4	15
20	16	<b>161 490 702</b>	0.015	38	14	16	34	4	18
25	16	<b>161 490 703</b>	0.021	44	19	20	39	5	20
32	16	<b>161 490 704</b>	0.031	53	24	26	42	5	20
40	16	<b>161 490 705</b>	0.050	65	31	33	45	5	19
50	16	<b>161 490 706</b>	0.082	77	39	41	53	6	22
63	16	<b>161 490 707</b>	0.161	99	49	51	62	7	24
75	16	<b>161 490 708</b>	0.302	125	58	65	74	9	30
90	16	<b>161 490 709</b>	0.467	150	70	90	80	10	28
110	16	<b>161 490 710</b>	0.747	180	86	100	88	11	27

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>