



**Valve end 546 Pro and 543 Pro PVC-U (G01)**  
**With solvent cement socket metric**

<b>d</b> (mm)	<b>PN</b> (bar)	<b>Code</b>	<b>Weight</b> (kg)	<b>D</b> (mm)	<b>D1</b> (mm)	<b>L</b> (mm)	<b>L1</b> (mm)	<b>z</b> (mm)
16	16	<b>161 490 666</b>	0.011	38	23	18	4	4
20	16	<b>161 490 667</b>	0.009	38	27	20	4	4
25	16	<b>161 490 668</b>	0.012	44	33	23	5	4
32	16	<b>161 490 669</b>	0.024	53	41	26	5	4
40	16	<b>161 490 670</b>	0.042	65	51	31	5	5
50	16	<b>161 490 671</b>	0.065	77	62	34	6	3
63	16	<b>161 490 672</b>	0.118	99	77	41	7	3
75	16	<b>161 490 673</b>	0.224	125	92	49	9	4
90	16	<b>161 490 674</b>	0.377	150	110	57	10	5
110	16	<b>161 490 675</b>	0.639	180	134	69	11	5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:  
 info.ps@georgfischer.com Internet: <http://www.gfps.com>