



**Cylindrical screen type 305 PVC-U**  
**Screen perforations 1.4 mm**

- For line strainers Type 305

d (mm)	DN (mm)	Size (inch)	kv-value ( $\Delta p=1$ bar) (L/min)	Code	SP	Weight (kg)	D (mm)	L (mm)	closest inch (inch)
20	15	½	35	<b>161 305 337</b>	10	0.003	14	39	½
25	20	¾	65	<b>161 305 387</b>	10	0.003	18	48	¾
32	25	1	90	<b>161 305 437</b>	5	0.003	24	60	1
40	32	1 ¼	155	<b>161 305 487</b>	2	0.004	30	71	1 ¼
50	40	1 ½	225	<b>161 305 537</b>	1	0.005	38	87	1 ½
63	50	2	370	<b>161 305 587</b>	2	0.008	48	106	2
75	65	2 ½	575	<b>161 305 637</b>	5	0.011	61	100	2 ½
90	80	3	955	<b>161 305 687</b>	2	0.013	73	118	3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>