



DN10/15 - 50



PROGEF Standard
Ball valve type 546
With mounting inserts
With fixed flanges serrated

Model:

- Material: PP-H
- For easy installation and removal
- Ball seat PTFE
- Integrated stainless steel mounting inserts
- z-dimension, valve end and union nut are not compatible with type 346

Option:

- Individual configuration of the valve
- Multifunctional module with integrated limit switches
- Pneumatic or electric actuators from GF

d (mm)	Size (inch)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (L/min)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
20	½	15	10	185	167 546 182	1	0.245	167 546 192	1	0.245
25	¾	20	10	350	167 546 183	1	0.345	167 546 193	1	0.345
32	1	25	10	700	167 546 184	1	0.492	167 546 194	1	0.495
40	1 ¼	32	10	1000	167 546 185	1	0.820	167 546 195	1	0.824
50	1 ½	40	10	1600	167 546 186	1	1.052	167 546 196	1	1.066
63	2	50	10	3100	167 546 187	1	1.751	167 546 197	1	1.751

d (mm)	D (mm)	D1 (mm)	D3 (mm)	H (mm)	H1 (mm)	H2 (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	L5 (mm)	L6 (mm)	M
20	95	65	14	57	27	12	120	77	56	130	25	32	45	M6
25	105	75	14	67	30	12	140	97	65	150	25	39	58	M6
32	115	85	14	73	36	12	150	97	71	160	25	39	58	M6
40	140	100	18	90	44	15	170	128	85	180	45	54	74	M8
50	150	110	18	97	51	15	190	128	89	200	45	54	74	M8
63	165	125	18	116	64	15	220	152	101	230	45	66	87	M8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>