



**Angle seat check valve type 303 PVC-U silicone free
With solvent cement spigots metric**

Model:

- For horizontal or vertical installation
- Leakproof even at minimum pressure
- Silicone free/paint-compatible
- Overall length EN 558

d (mm)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (L/min)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
16	10	10	41	161 303 015	1	0.094	161 303 040	1	0.094
20	15	10	95	161 303 016	1	0.139	161 303 041	1	0.132
25	20	10	180	161 303 017	1	0.200	161 303 042	1	0.200
32	25	10	327	161 303 018	1	0.323	161 303 043	1	0.323
40	32	10	484	161 303 019	1	0.498	161 303 044	1	0.498
50	40	10	725	161 303 020	1	0.860	161 303 045	1	0.860
63	50	10	1130	161 303 021	1	1.455	161 303 046	1	1.455
75	65	10	1700	161 303 022	1	2.483	161 303 047	1	2.450
90	80	10	2500	161 303 023	1	3.511	161 303 048	1	3.511

d (mm)	D (mm)	H (mm)	L (mm)	L1 (mm)	L2 (mm)	closest inch (inch)
16	39	58	114	120	24	3/8
20	43	65	124	130	28	1/2
25	47	75	144	150	37	3/4
32	56	90	154	160	37	1
40	64	102	174	180	44	1 1/4
50	82	123	194	200	48	1 1/2
63	95	144	224	230	60	2
75	92	186	284	290	74	2 1/2
90	104	204	300	310	85	3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>