



PROGEF Plus pipe SDR11/PN10/S5

Model:

- Material: PP-H - homopolymer
- dimensions: acc. to DIN 8077/78
- Colour: light grey RAL 7032
- Pipe length: 5000mm, with plain ends
- High Purity-Quality
- both ends closed with caps, double bagged into foil
- **Note 1:** DIBT Z-40.23-4 Approval
- Attention: Pressure rates refer to operating temperatures at 20°C. Higher temperatures and aggressive flow media reduce pressure load (see above DIN and our technical documentation). Pressure load capacity has to be determined in consideration with safety demands of the respective applications and calculated in accordance.

Note	d (mm)	SDR	PN (bar)	Code	Weight (kg/m)	e (mm)
1	20	11	10	167 481 711	0.107	1.9
1	25	11	10	167 481 712	0.164	2.3
1	32	11	10	167 481 713	0.261	2.9
1	40	11	10	167 481 714	0.412	3.7
1	50	11	10	167 481 715	0.638	4.6
1	63	11	10	167 481 716	1.010	5.8
1	75	11	10	167 481 717	1.410	6.8
1	90	11	10	167 481 718	2.030	8.2
1	110	11	10	167 481 719	3.010	10.0
1	125	11	10	167 481 720	3.910	11.4
1	140	11	10	167 481 721	4.870	12.7
1	160	11	10	167 481 722	6.380	14.6
	180	11	10	167 481 723	8.070	16.4
	200	11	10	167 481 724	9.950	18.2
	225	11	10	167 481 725	12.600	20.5
	250	11	10	167 481 726	15.500	22.7
	280	11	10	167 481 727	19.400	25.4
	315	11	10	167 481 728	24.600	28.6
	355	11	10	167 481 730	31.200	32.2
	400	11	10	167 481 731	39.600	36.3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>