




**Single union safeblock ISO PVC-U**  
**Ball valve with solvent cement sockets**



d (mm)	d (inch)	DN (mm)	PN (bar)	EPDM Code	SP	Weight (kg)	L1 (mm)	M (mm)	A (mm)	S (mm)	H (mm)	L2 (mm)	Z (mm)
16		10	16	VSA18I160	1	0.095	14	40	50	19	53	76	48
20		15	16	VSA18I200	1	0.099	16	40	50	19	53	80	48
25		20	16	VSA18I250	1	0.155	19	45	59	19	60	91	53
32		25	16	VSA18I320	1	0.234	22	51	68	21	67	102	58
40		32	16	VSA18I400	1	0.350	26	59	80	25	79	120	68
50		40	16	VSA18I500	1	0.534	31	70	94	28	90	140	78
63		50	16	VSA18I630	1	0.893	38	84	115	29	107	169	93
75	2 ½	65	10	VSA18I750	1	1.640	44	103	145	32	129	206	118
90		80	10	VSA18I900	1	2.576	51	120	168	36	143	242	140
110		100	10	VSA18I910	1	4.772	61	141	210	43	169	282	160

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>