




**ecoFIT Elbow 45° PE100**  
d20-225mm / SDR11

**Model:**

- Conventional butt-welding according to DVS 2207
- IR = Infrared-(IR Plus) compatible. Choose fusion parameters: PE100



d (mm)	DN (mm)	PN (bar)	FM	Code	Weight (kg)	Lmax (mm)	Q1 (mm)	s1 (mm)	z (mm)
20	15	16	IR	<b>753 158 606</b>	0.007	61.70	24	1.9	8
25	20	16	IR	<b>753 158 607</b>	0.013	66.88	25	2.3	9
32	25	16	IR	<b>753 158 608</b>	0.019	72.77	25	2.9	11
40	32	16	IR	<b>753 158 609</b>	0.036	80.72	25	3.7	14
50	40	16	IR	<b>753 158 610</b>	0.059	89.38	26	4.6	16
63	50	16	IR	<b>753 158 611</b>	0.103	102.51	29	5.8	18
75	65	16	IR	<b>753 158 612</b>	0.146	110.16	29	6.8	20
90	80	16	IR	<b>753 158 613</b>	0.241	127.42	34	8.2	23
110	100	16	IR	<b>753 158 614</b>	0.442	158.39	43	10.0	27
125	100	16	IR	<b>753 158 615</b>	0.638	179.06	48	11.4	31
140	125	16	IR	<b>753 158 616</b>	0.902	199.72	55	12.7	33
160	150	16	IR	<b>753 158 617</b>	1.340	227.28	60	14.6	40
200	200	16	IR	<b>753 158 619</b>	2.612	282.39	75	18.2	49
225	200	16	IR	<b>753 158 620</b>	3.638	318.54	85	20.5	55

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>