




Solenoid pilot valve type MNL532
3/2- & 5/2-way for single and double acting actuators
with NAMUR interface

Model:

- With NAMUR connection and two silencers/throttle screws
- Electrical connection: Cable plug B
- Material of body: Aluminum

Mode of action:

- 3/2-way valve, in rest position pressure inlet 1 closed, outlet 3 exhausted
- 5/2-way valve, in rest position pressure inlet 1 connected to outlet 4, outlet 3 exhausted
- **for pneumatic actuators**



DN	Size	PN	kv-value	Compressed	Voltage	NBR	SP	Weight
(mm)	(inch)	(bar)	($\Delta p=1$ bar)	air connection		Code		(kg)
			(L/min)	P				
5	1/4	10	950	G 1/4	230 V, AC	199 190 360	1	0.332
5	1/4	10	950	G 1/4	110 V, AC	199 190 359	1	0.343
5	1/4	10	950	G 1/4	48 V, AC	199 190 361	1	0.341
5	1/4	10	950	G 1/4	24 V, AC	199 190 358	1	0.339
5	1/4	10	950	G 1/4	24 V, DC	199 190 357	1	0.343

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>