



## PROGEF Standard Union PN10

### Model:

- Material: PP-H
- Fusion socket metric
- Jointing face: With O-ring groove
- **For the dimensions d75-110 please see instructions for the installation**

d75-d110 new thread design since 2022

d (mm)	PN (bar)	EPDM Code	FKM Code	Weight (kg)
16	10	727 510 155	727 520 155	0.020
20	10	727 510 156	727 520 156	0.038
25	10	727 510 157	727 520 157	0.062
32	10	727 510 158	727 520 158	0.080
40	10	727 510 159	727 520 159	0.137
50	10	727 510 160	727 520 160	0.136
63	10	727 510 161	727 520 161	0.251
75	10	727 510 192	727 520 192	0.427
90	10	727 510 193	727 520 193	0.625
110	10	727 510 194	727 520 194	1.161

d (mm)	L1 (mm)	L2 (mm)	D (mm)	G (inch)	z1 (mm)	z2 (mm)	Size	O-Ring EPDM	O-Ring FKM
16	18	24	35	3/4	3	9	15,54 x 2,62	748.410.005	749.410.005
20	19	26	48	1	3	10	20,22 x 3,53	748.410.006	749.410.006
25	21	28	58	1 1/4	3	10	28,17 x 3,53	748.410.007	749.410.007
32	23	30	65	1 1/2	3	10	32,93 x 3,53	748.410.008	749.410.008
40	25	34	79	2	3	12	40,65 x 5,34	748.410.009	749.410.009
50	28	39	91	2 1/4	3	14	46,99 x 5,34	748.410.010	749.410.010
63	32	47	111	2 3/4	3	18	59,69 x 5,34	748.410.011	749.410.011
75	36	51	138	S110x5	3	18	74,63 x 5,34	748.410.383	749.410.383
90	42	55	161	S130x5	5	18	94,62 x 5,34	748.410.248	749.410.248
110	49	54	191	S155x5	6	12	114,7 x 6,99	748.410.384	749.410.384

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>