



Reducing bush PVC-U R Rp

Model:

- With taper male thread R and parallel female thread Rp
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

Thread Type	Size (inch)	Thread Type 2	Size 2 (inch)	PN (bar)	Code	SP	Weight (kg)	z (mm)	L (mm)	s (mm)
R	½	Rp	¾	10	721 910 834	10	0.014	25	36	27
R	¾	Rp	1	10	721 910 837	10	0.021	25	39	32
R	1	Rp	1 ½	10	721 910 842	10	0.029	31	45	32
R	1	Rp	¾	10	721 910 841	10	0.031	29	45	36
R	1 ¼	Rp	1	10	721 910 846	10	0.050	32	50	46
R	1 ½	Rp	1 ¼	10	721 910 852	10	0.065	35	55	55
R	2	Rp	1 ½	10	721 910 858	5	0.127	45	65	65

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>