



## Tee 90° PVC-U metric Rp

### Model:

- With solvent cement socket metric, branch with parallel female thread Rp
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

d (mm)	Thread Type	Size (inch)	PN (bar)	Code	SP	Weight (kg)	z1 (mm)	z2 (mm)	D (mm)	D1 (mm)	L (mm)
12	Rp	1/4	16	<b>721 200 204</b>	10	0.015	7	7	17	20	19
16	Rp	3/8	16	<b>721 200 205</b>	10	0.027	9	9	21	25	23
20	Rp	1/2	16	<b>721 200 206</b>	10	0.029	11	13	26	30	29
25	Rp	3/4	16	<b>721 200 207</b>	10	0.043	14	15	32	35	33
32	Rp	1	16	<b>721 200 208</b>	10	0.080	17	19	40	45	39
40	Rp	1 1/4	16	<b>721 200 209</b>	10	0.134	23	26	47	55	49
50	Rp	1 1/2	16	<b>721 200 210</b>	5	0.212	27	36	59	59	59
63	Rp	2	16	<b>721 200 211</b>	5	0.379	33	46	74	75	71

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland  
 Phone +41 -(0)52-631 1111  
 e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)  
 Internet: <http://www.gfps.com>