



**Valve end 546 Pro and 543 Pro PVC-U (G06)
With threaded socket Rp**

Model:

- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVC-U

Rp (inch)	PN (bar)	Code	Weight (kg)	z (mm)	D1 (mm)	D (mm)	L (mm)	L1 (mm)
3/8	10	161 490 690	0.011	7	24	38	20	4
1/2	10	161 490 691	0.013	6	28	38	22	4
3/4	10	161 490 692	0.019	7	34	44	25	5
1	10	161 490 693	0.031	7	42	53	28	5
1 1/4	10	161 490 694	0.047	7	52	65	30	5
1 1/2	10	161 490 695	0.074	9	63	77	32	6
2	10	161 490 696	0.129	10	78	99	38	7
2 1/2	10	161 490 697	0.255	18	92	125	49	9
3	10	161 490 698	0.436	23	110	150	57	10
4	10	161 490 699	0.645	29	134	180	69	11

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>