



**Valve end 546 Pro and 543 Pro PVC-U (G08)
With threaded socket Rc**

Model:

- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVC-U

PN (bar)	Rc (inch)	Code	Weight (kg)	D (mm)	D1 (mm)	L (mm)	L1 (mm)	z (mm)
10	½	161 490 755	0.013	38	28	22	4	5
10	¾	161 490 756	0.019	44	34	25	5	7
10	1	161 490 757	0.041	53	42	28	5	7
10	1 ¼	161 490 758	0.047	65	52	30	5	6
10	1 ½	161 490 759	0.081	77	63	32	6	8
10	2	161 490 760	0.145	99	78	38	7	9
10	2 ½	161 490 761	0.261	125	58	49	9	18
10	3	161 490 762	0.444	150	110	57	10	23
10	4	161 490 763	0.682	180	134	69	11	29

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>