


TP Reduced tee 90° PVC-U metric



d - d1 (mm)	PN (bar)	Code	SP	GP	Weight (kg)	Z1 (mm)	Z2 (mm)	L1 (mm)	L2 (mm)	E2 (mm)	E1 (mm)
20 - 16	16	RV0TRI20A	10	200	0.024	11	11	16	14	23	28
25 - 16	16	RV0TRI25A	10	120	0.039	14	14	19	14	23	34
25 - 20	16	RV0TRI25B	10	120	0.040	14	14	19	16	28	34
32 - 16	16	RV0TRI32A	10	140	0.063	17	17	22	14	23	42
32 - 20	16	RV0TRI32B	10	140	0.068	17	17	22	16	28	42
32 - 25	16	RV0TRI32C	10	140	0.068	17	17	22	19	34	42
40 - 20	16	RV0TRI40B	1	100	0.107	21	21	26	16	28	51
40 - 25	16	RV0TRI40C	1	100	0.108	21	21	26	19	34	51
40 - 32	16	RV0TRI40D	1	100	0.112	21	21	26	22	42	51
50 - 20	16	RV0TRI50B	1	50	0.155	26	26	31	16	28	61
50 - 25	16	RV0TRI50C	1	50	0.160	26	26	31	19	34	61
50 - 32	16	RV0TRI50D	1	50	0.161	26	26	31	22	42	61
50 - 40	16	RV0TRI50E	1	50	0.173	26	26	31	26	51	61
63 - 20	16	RV0TRI63B	1	30	0.257	33	33	38	16	28	75
63 - 25	16	RV0TRI63C	1	30	0.262	33	33	38	19	34	75
63 - 32	16	RV0TRI63D	1	30	0.274	33	33	38	22	42	75
63 - 40	16	RV0TRI63E	1	30	0.270	33	33	38	26	51	75
63 - 50	16	RV0TRI63F	1	30	0.278	33	33	38	31	61	75
75 - 32	16	RV0TRI75D	1	18	0.455	39	39	44	22	42	89
75 - 40	16	RV0TRI75E	1	45	0.460	39	39	44	26	51	89
75 - 50	16	RV0TRI75F	1	18	0.458	39	39	44	31	61	89
75 - 63	16	RV0TRI75G	1	30	0.471	39	39	44	38	75	89
90 - 40	16	RV0TRI90E	1	30	0.692	47	47	51	26	61	106
90 - 50	16	RV0TRI90F	1	28	0.703	47	47	51	31	61	106
90 - 63	16	RV0TRI90G	1	24	0.707	47	47	51	38	75	106
90 - 75	16	RV0TRI90H	1	24	0.731	47	47	51	44	89	106
110 - 50	16	RV0TRI91F	1	16	1.228	57	57	61	31	61	129
110 - 63	16	RV0TRI91G	1	16	1.231	57	57	61	38	75	129
110 - 75	16	RV0TRI91H	1	16	1.245	57	57	61	44	89	129
110 - 90	16	RV0TRI91I	1	14	1.302	57	57	61	51	106	129
125 - 63	16	RV0TRI92G	1	9	1.955	66	66	69	38	75	148
125 - 90	16	RV0TRI92I	1	9	1.737	66	66	69	51	106	148
125 - 110	16	RV0TRI92L	1	8	1.827	66	66	69	61	129	148
160 - 90	16	RV0TRI94I	1	4	3.771	82	82	86	51	106	190
160 - 110	16	RV0TRI94L	1	4	3.819	82	82	86	61	129	190

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>