



PROGEF Standard Diaphragm valve type 317
With flanges Inch ANSI

Model:


- Material: PP-H
- Joining faces serrated
- Connecting dimension: ISO 7005 / EN 1092 / DIN 25 PN10 / BS4504
- DN65 with PP-V backing flange
- DN80-150 with fixed flange

Option:


- Handwheel lockable DN65 (basic version not lockable)
- * **DN80 and DN150 fixed flanges metric and inch ANSI B16.5**

	d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	EPDM Code	Weight (kg)	PTFE with EPDM supporting diaphragm Code	Weight (kg)
		65	2 1/2	10	992	167 317 523	4.605	167 317 538	4.000
*	90	80	3	10	1700	167 317 024	8.689	167 317 039	8.088
	110	100	4	10	2700	167 317 325	11.238	167 317 340	11.300
*	160	150	6	6	6033	167 317 027	24.707	167 317 042	25.000


	D (mm)	D1 (mm)	D2 (mm)	D3 (mm)	H (mm)	H1 (mm)	H2 (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	M	Lift = Hx (mm)	AL
	185	140	152	19	210	46	15	290		70		8	35	4
*	200	160	270	18	265	57	23	310	35	120		12	40	8
	225	180	270	18	304	69	23	350	38	120		12	50	8
*	282	241	400	23	437	108	23	480	29	100	200	12	70	8



DN 15-65



DN 80-100



DN 150

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>