



Elbow 45° ABS metric

- >d225 - maximum operating temperature: +40°C

d (mm)	d (inch)	Size (inch)	PN (bar)	Code	SP	Weight (kg)	closest inch (inch)	z (mm)	D (mm)	L (mm)
20			16	729 150 106	10	0.009	½	5	25	21
25			16	729 150 107	10	0.013	¾	6	31	25
32			10	729 150 108	10	0.026	1	8	40	30
40			10	729 150 109	10	0.044	1 ¼	10	49	36
50			10	729 150 110	5	0.079	1 ½	12	61	43
63			10	729 150 111	10	0.143	2	14	76	52
75	2 ½	2 ½	10	729 150 112	5	0.225	2 ½	17	89	61
90			10	729 150 113	4	0.363	3	20	107	71
110			10	729 150 114	10	0.567	4	28	131	89
140	5	5	10	729 150 116	1	1.175	5	32	162	108
160			10	729 150 117	4	1.713	6	36	185	122
200			10	729 150 119	1	2.546	8	43	225	149
225			10	729 150 120	1	3.162	8	49	250	168

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>