




Air release/foot valve ISO PVC-U
With solvent cement sockets

- (*)Body and dimensions = 3"
- Standards:ISO 727, EN 1452, DIN 8063, NF T54-028, BS 4346/1



d	d	DN	PN	EPDM	SP	Weight	Z	A	L1	L2
(mm)	(inch)	(mm)	(bar)	Code		(kg)	(mm)	(mm)	(mm)	(mm)
16		10	16	VRV21I160	1	0.132	48	50	14	76
20		15	16	VRV21I200	1	0.125	48	50	16	80
25		20	16	VRV21I250	1	0.197	53	59	19	91
32		25	16	VRV21I320	1	0.273	58	68	22	102
40		32	16	VRV21I400	1	0.398	68	80	26	120
50		40	16	VRV21I500	1	0.597	78	94	31	140
63		50	16	VRV21I630	1	1.016	93	115	38	169
*	75	2 ½	65	VRV21I750	1	2.985	118	168	44	206
90		80	10	VRV21I900	1	3.050	140	168	51	242

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>