

Data sheet


valid from: 2/14/23



Check valve ISO PVC-U With solvent cement sockets

Model:

- Rubber spring
- Standards:ISO 727, EN 1452, DIN 8063, NF T54-028, BS 4346/1
- (*)Body and dimensions = 3"



d (mm)	d (inch)	DN (mm)	PN (bar)	EPDM Code	SP	Weight (kg)	L1 (mm)	L2 (mm)	A (mm)	X (mm)	Z (mm)	
16		10	16	VR0211160	1	0.133	14	76	50	42	48	
20		15	16	VR0211200	1	0.125	16	80	50	42	48	
25		20	16	VR0211250	1	0.196	19	91	59	48	53	
32		25	16	VR0211320	1	0.245	22	102	68	54	58	
40		32	16	VR0211400	1	0.375	26	120	80	62	68	
50		40	16	VR0211500	1	0.610	31	140	94	72	78	
63		50	16	VR0211630	1	1.030	38	169	115	86	93	
*	75	2 1/2	65	10	VR0211750	1	3.028	44	206	168	110	118
90		80	10	VR0211900	1	3.054	51	242	168	128	140	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>