




## Elbow 90° PVC-C metric Rp

### Model:

- With solvent cement socket metric and parallel female thread Rp
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-C



Rp (inch)	d (mm)	PN (bar)	Code	SP	Weight (kg)	z1 (mm)	z2 (mm)	D (mm)	L (mm)
½	20	16	<b>723 100 206</b>	10	0.024	11	14	30	27
¾	25	16	<b>723 100 207</b>	10	0.037	14	17	35	33
1	32	16	<b>723 100 208</b>	10	0.063	17	22	45	39
1 ¼	40	16	<b>723 100 209</b>	10	0.134	23	27	55	50
1 ½	50	16	<b>723 100 210</b>	5	0.199	27	36	62	58
2	63	16	<b>723 100 211</b>	10	0.337	33	46	75	73

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>