




**ecoFIT Adaptor nipple PE100**  
**d20-63mm / SDR11 / Male thread R**

**Model:**

- With butt fusion spigot SDR11 and tapered male thread
- Do not use thread sealing pastes that are harmful to PE
- Install with low mechanical stress and avoid large cyclic temperature changes



d (mm)	Thread Type	Size (inch)	DN (mm)	PN (bar)	FM	Code	Weight (kg)	Lmax (mm)	Q1 (mm)	s1 (mm)	SLW (mm)
20	R	½	15	16	IR	<b>753 910 556</b>	0.013	51	23	1.9	32
25	R	¾	20	16	IR	<b>753 910 557</b>	0.026	52	23	2.3	36
32	R	1	25	16	IR	<b>753 910 558</b>	0.028	55	23	3.0	46
40	R	1 ¼	32	16	IR	<b>753 910 559</b>	0.043	58	23	3.7	55
50	R	1 ½	40	16	IR	<b>753 910 560</b>	0.063	60	23	4.6	65
63	R	2	50	16	IR	<b>753 910 561</b>	0.104	67	26	5.8	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>