



**SYGEF Plus Adaptor socket with female thread NPT**  
**SDR21/PN16**  
**High Purity clean-room product ISO Class 5 (100)**

**Model:**

- Material: PVDF-HP
- With butt fusion spigot and taper female thread NPT
- Avoid stresses when installing and large changes in temperature
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVDF

**Note:**

\* Please keep strictly to the GF internal installation preferences

d	Thread Type	Size	PN	FM	Code	Weight	L	L1	s	e	
(mm)		(inch)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	
20	NPT	¾	16	BCF, IR	<b>735 914 785</b>	0.029	54	30	32	1.9	
20	NPT	½	16	BCF, IR	<b>735 914 786</b>	0.027	54	30	32	1.9	
25	NPT	¾	16	BCF, IR	<b>735 914 787</b>	0.033	58	30	38	1.9	
32	NPT	1	16	BCF, IR	<b>735 914 788</b>	0.066	63	30	48	2.4	
40	NPT	1 ¼	16	BCF, IR	<b>735 914 789</b>		67	30	58	2.4	
50	NPT	1 ½	16	BCF, IR	<b>735 914 790</b>	0.108	67	30	65	3.0	
*	63	NPT	2	16	BCF, IR	<b>735 914 791</b>	0.190	73	30	80	3.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>