



Valve end 546 Pro and 543 Pro PVC-U (G07)
With threaded socket Rp reinforced

Model:

- Connection to plastic or metal threads
- Reinforcing ring stainless (A2)
- Do not use thread sealing pastes that are harmful to PVC-U

Rp	PN	Code	Weight	D	D1	L	L1	z
(inch)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
3/8	16	161 490 825	0.013	38	24	20	4	7
1/2	16	161 490 826	0.016	38	28	22	4	6
3/4	16	161 490 827	0.023	44	34	25	5	7
1	16	161 490 828	0.036	53	42	28	5	7
1 1/4	16	161 490 829	0.058	65	52	30	5	7
1 1/2	16	161 490 830	0.084	77	63	32	6	9
2	16	161 490 831	0.166	99	78	38	7	10

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>