




ecoFIT Adaptor socket PE80
d20-63mm / Female thread Rp

Model:

- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- With fusion socket metric and parallel female thread Rp, reinforced
- Do not use thread sealing pastes that are harmful to PE
- Install with low mechanical stress and avoid large cyclic temperature changes



d	Thread Type	Size	DN	PN	Code	Weight	Lmax	z	SLW
(mm)		(inch)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)
20	Rp	½	15	10	733 910 206	0.020	35	7	32
25	Rp	¾	20	10	733 910 207	0.026	39	7	36
32	Rp	1	25	10	733 910 208	0.042	45	7	46
40	Rp	1 ¼	32	10	733 910 209	0.068	53	7	55
50	Rp	1 ½	40	10	733 910 210	0.098	54	9	65
63	Rp	2	50	10	733 910 211	0.155	62	9	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>