

JOINT PLAT

EVA


FLAT GASKET

JUNTA PLANA

VLAKKE AFDICHTING



Référence	Ø	D	A	B	C
JP25	25	2	25	75	39
JP32	32	2	32	85	48
JP40	40	2	40	100	59
JP50	50	3	50,5	110	73
JP63	63	3	64	125	87
JP75	75	3	78	145	103
JP90	90	3	91	160	123
JP110	110	4	110	180	147
JP125	125	4	125	190	163
JP140	140	4	140	210	185
JP160	160	4	160	240	209
JP200	200	5	200	295	244
JP225	225	5	225	295	273
JP250	250	5	250	350	325
JP315	315	5	315	400	375
JP355 ¹	355	5	340	-	430
JP400 ¹	400	4	402	515	479

¹ = Joint EPDM

INFORMATION TECHNIQUE

UTILISATION

Adduction d'eau potable, industrie, irrigation, arrosage et piscine.

MATÉRIAUX

EVA du diamètre 25mm au 315mm, EPDM du diamètre 355mm au diamètre 400mm.

TEMPÉRATURE DE SERVICE

Température maximum de travail 0°C à 45°C pour l'EVA et - 20°C à 120°C pour l'EPDM.



PRODUIT

+ Oreilles de centrage