
Data sheet

valid from: 2/13/23





TP Threaded reducer R-Rp PVC-U

R (inch)	Rp (inch)	PN (bar)	Code	SP	GP	Weight (kg)	O (mm)	Z (mm)	L1 (mm)	L2 (mm)	E (mm)
½	⅜	16	**RV0RIF20A**	10	400	0.012	24	24	15.0	11.4	32
¾	⅜	16	**RV0RIF25A**	10	280	0.016	30	25	16.3	11.4	23
¾	½	16	**RV0RIF25B**	10	280	0.018	30	26	16.3	15.0	28
1	⅜	16	**RV0RIF32A**	10	160	0.024	36	28	19.1	11.4	23
1	½	16	**RV0RIF32B**	10	160	0.025	36	29	19.1	15.0	28
1	¾	16	**RV0RIF32C**	10	160	0.026	36	30	19.1	16.3	34
1 ¼	½	16	**RV0RIF40B**	1	150	0.041	46	33	21.4	15.0	28
1 ¼	¾	16	**RV0RIF40C**	1	150	0.044	46	33	21.4	16.3	34
1 ¼	1	16	**RV0RIF40D**	1	150	0.045	46	33	21.4	19.1	42
1 ½	¾	16	**RV0RIF50C**	1	120	0.047	50	34	21.4	16.3	34
1 ½	1	16	**RV0RIF50D**	1	100	0.049	50	34	21.4	19.1	42
1 ½	1 ¼	16	**RV0RIF50E**	1	100	0.056	55	34	21.4	21.4	51
2	1	16	**RV0RIF63D**	1	140	0.084	65	37	25.7	19.1	42
2	1 ¼	16	**RV0RIF63E**	1	140	0.083	65	37	25.7	21.4	51
2	1 ½	16	**RV0RIF63F**	1	130	0.091	65	37	25.7	21.4	58
2 ½	1 ¼	16	**RV0RIF75E**	1	170	0.137	80	43	30.2	21.4	51
2 ½	1 ½	16	**RV0RIF75F**	1	170	0.136	80	43	30.2	21.4	58
2 ½	2	16	**RV0RIF75G**	1	150	0.140	80	43	30.2	25.7	72
3	1 ½	16	**RV0RIF90F**	1	150	0.203	95	47	33.3	21.4	58
3	2	16	**RV0RIF90G**	1	125	0.206	95	47	33.3	25.7	72
3	2 ½	16	**RV0RIF90H**	1	115	0.216	95	47	33.3	30.2	89
4	2	16	**RV0RIF91G**	1	85	0.325	120	53	39.3	25.7	72
4	2 ½	16	**RV0RIF91H**	1	42	0.331	120	53	39.3	30.2	89
4	3	16	**RV0RIF91I**	1	60	0.342	120	53	39.3	33.3	103

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
Phone +41 -(0)52-631 1111
e-mail: info.ps@georgfischer.com
Internet: http://www.gfps.com