



Cap PVC-U Rp

Model:

- With parallel female thread Rp
- Connection to plastic thread only
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

Thread Type	Size (inch)	PN (bar)	Code	SP	Weight (kg)	D (mm)	L (mm)	s (mm)
Rp	3/8	10	721 960 605	10	0.012	31	19	27
Rp	1/2	10	721 960 606	10	0.018	37	21	32
Rp	3/4	10	721 960 607	10	0.024	42	24	36
Rp	1	10	721 960 608	10	0.040	50	26	46
Rp	1 1/4	10	721 960 609	10	0.060	60	29	55
Rp	1 1/2	10	721 960 610	10	0.072	65	31	60
Rp	2	10	721 960 611	5	0.127	81	36	75

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>