



Socket ABS metric

- >d225 - maximum operating temperature: +40°C

d (mm)	PN (bar)	Code	SP	Weight (kg)	D (mm)	L (mm)	z (mm)	closest inch (inch)
20	16	729 910 106	10	0.007	26	35	3	½
25	16	729 910 107	10	0.012	32	41	3	¾
32	10	729 910 108	10	0.020	40	47	3	1
40	10	729 910 109	10	0.035	49	55	3	1 ¼
50	10	729 910 110	10	0.060	61	65	3	1 ½
63	10	729 910 111	10	0.110	76	79	3	2
75	10	729 910 112	20	0.145	87	92	4	2 ½
90	10	729 910 113	10	0.241	104	107	5	3
110	10	729 910 114	5	0.566	131	132	5	4
140	10	729 910 116	2	0.813	162	159	7	5
160	10	729 910 117	2	1.176	183	180	8	6
200	10	729 910 119	1	1.511	221	221	9	8
225	10	729 910 120	1	2.537	253	248	10	8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>