



*



Diaphragm valve type 317 PVC-U With flanges PVC-U Inch ANSI

Model:

- Flat sealing faces
- Overall length according to EN 558
- Connecting dimension: ANSI/ASME B 16.5 class 150, ASTM D 4024, BS 1560, BS EN 1759


Option:

- Handwheel lockable DN65 (basic version not lockable)


* **DN80, DN100 and DN150 fixed flanges metric and inch ANSI B16.5**

	d (mm)	DN (mm)	Size (inch)	PN (bar)	NBR Code	EPDM Code	FKM Code	PTFE with EPDM supp. diaphragm Code	Weight (kg)
	75	65	2 1/2	10	161 317 608	161 317 623	161 317 668	161 317 638	4.300
*	90	80	3	10	161 317 009	161 317 024	161 317 069	161 317 039	10.251
*	110	100	4	6	161 317 010	161 317 025	161 317 070	161 317 040	13.382
*	160	150	6	6	161 317 012	161 317 027	161 317 072	161 317 042	35.000


	D (mm)	D1 (mm)	D2 (mm)	D3 (mm)	H (mm)	H1 (mm)	H2 (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	M	Lift = Hx (mm)	AL
	185	140	152	19	201	46	15	290		70		M8	30	4
*	200	160	270	18	265	57	23	310	35	120		M12	40	8
*	225	180	270	18	304	69	23	350	35	120		M12	50	8
*	285	240	400	23	437	108	23	480	26	100	200	M12	70	8



DN 15-65



DN 80-100



DN 150

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>