


Data sheet

valid from: 4/2/26









COOL-FIT ABS Plus Tee 90° reduced PN10

Model:

- Pre-insulated ABS metric
- Insulation made from PUR
- Outer jacket impact resistant.Color: black

d (mm)	d1 (mm)	D (mm)	D1 (mm)	Type	PN (bar)	Code	Weight (kg)
32	25	90	90	C	10	**738 201 038**	0.282
40	25	110	90	C	10	**738 201 051**	0.433
40	32	110	90	C	10	**738 201 047**	0.460
50	25	110	90	C	10	**738 201 092**	0.475
50	32	110	90	C	10	**738 201 064**	0.489
63	25	125	90	C	10	**738 201 093**	0.668
63	32	125	90	C	10	**738 201 078**	0.668
63	50	125	110	C	10	**738 201 070**	0.802
75	40	140	110	A	10	**738 201 182**	1.091
90	32	160	90	C	10	**738 201 043**	1.495
90	63	160	125	C	10	**738 201 046**	1.597
110	32	180	90	B	10	**738 201 144**	1.783
110	50	180	110	B	10	**738 201 136**	1.841
140	50	225	110	B	10	**738 201 148**	3.229
140	75	225	140	B	10	**738 201 149**	3.342
160	110	250	180	B	10	**738 201 152**	4.885
200	110	280	180	C	10	**738 201 153**	7.799
225	110	315	180	C	10	**738 201 156**	9.237
225	160	315	250	C	10	**738 201 157**	9.968

d (mm)	d1 (mm)	z (mm)	z1 (mm)	required Nipple	Closest inch (inch)
32	25	80	80	1x738901607; 2x738901608	1 - ¾
40	25	90	90	1x738901607; 2x738901609	1 ¼ - ¾
40	32	90	90	1x738901608; 2x738901609	1 ¼ - 1
50	25	90	90	1x738901607; 2x738901610	1 ½ - ¾
50	32	90	90	1x738901608; 2x738901610	1 ½ - 1
63	25	100	100	1x738901607; 2x738901611	2 - ¾
63	32	100	100	1x738901608; 2x738901611	2 - 1
63	50	100	100	1x738901610; 2x738901611	2 - 1 ¼
75	40	115	110	1x738901109; 2x738901112	2 ½ - 1 ¼
90	32	140	140	1x738901608; 2x738901613	3 - 1
90	63	140	140	1x738901611; 2x738901613	3 - 2
110	32	117	130	1x738901108; 2x738901614	4 - 1
110	50	117	130	1x738901110; 2x738901614	4 - 1 ½
140	50	147	153	1x738901110; 2x738901616	5 - 1 ½
140	75	147	153	1x738901112; 2x738901616	5 - 2 ½
160	110	167	165	1x738901114; 2x738901617	6 - 4
200	110	213	193	1x738901614; 2x738901619	8 - 4
225	110	239	206	1x738901614; 2x738901620	8 - 4
225	160	239	206	1x738901617; 2x738901620	8 - 6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com