




## Blanking flange set PP-H Combined jointing face flat and serrated metric

### Model:

- d63 - d315: backing flange PP-V with end blank PP-H
- d355 - d630: backing flange PP/Steel with end blank PP-H
- Connecting dimensions: ISO 7005, EN 1092, DIN 2501
- **Bolt circle PN 10**

AL: number of holes

L: height backing ring + collar thickness end blank



| d    | DN   | PN    | Code               | Weight | D    | D1   | D2   | D3   | D4   | L    | L1   | H    | AL |
|------|------|-------|--------------------|--------|------|------|------|------|------|------|------|------|----|
| (mm) | (mm) | (bar) |                    | (kg)   | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) |    |
| 63   | 50   | 10    | <b>727 700 611</b> | 0.531  | 75   | 125  | 165  | 18   | 102  | 38   | 14   | 24   | 4  |
| 75   | 65   | 10    | <b>727 700 612</b> | 0.901  | 89   | 145  | 185  | 18   | 122  | 42   | 16   | 26   | 4  |
| 90   | 80   | 10    | <b>727 700 613</b> | 1.054  | 105  | 160  | 200  | 18   | 138  | 44   | 17   | 27   | 8  |
| 110  | 100  | 10    | <b>727 700 614</b> | 1.199  | 125  | 180  | 220  | 18   | 158  | 46   | 18   | 28   | 8  |
| 125  | 100  | 10    | <b>727 700 615</b> | 1.201  | 132  | 180  | 220  | 18   | 158  | 53   | 25   | 28   | 8  |
| 140  | 125  | 10    | <b>727 700 616</b> | 1.748  | 155  | 210  | 250  | 18   | 188  | 55   | 25   | 30   | 8  |
| 160  | 150  | 10    | <b>727 700 617</b> | 2.312  | 175  | 240  | 285  | 22   | 212  | 57   | 25   | 32   | 8  |
| 180  | 150  | 10    | <b>727 700 618</b> | 2.443  | 180  | 240  | 285  | 22   | 212  | 62   | 30   | 32   | 8  |
| 200  | 200  | 10    | <b>727 700 619</b> | 3.961  | 232  | 295  | 340  | 22   | 268  | 66   | 32   | 34   | 8  |
| 225  | 200  | 10    | <b>727 700 620</b> | 3.956  | 235  | 295  | 340  | 22   | 268  | 66   | 32   | 34   | 8  |
| 250  | 250  | 10    | <b>727 700 621</b> | 5.425  | 285  | 350  | 395  | 22   | 320  | 73   | 35   | 38   | 12 |
| 280  | 250  | 10    | <b>727 700 622</b> | 19.781 | 291  | 350  | 395  | 22   | 320  | 73   | 35   | 38   | 12 |
| 315  | 300  | 10    | <b>727 700 623</b> | 8.602  | 335  | 400  | 445  | 22   | 370  | 77   | 35   | 42   | 12 |
| 355  | 350  | 10    | <b>727 700 624</b> | 23.184 | 373  | 460  | 515  | 22   | 430  | 80   | 40   | 40   | 16 |
| 400  | 400  | 10    | <b>727 700 625</b> | 30.304 | 427  | 515  | 574  | 26   | 482  | 86   | 46   | 40   | 16 |
| 450  | 500  | 10    | <b>727 700 626</b> | 43.485 | 510  | 620  | 684  | 26   | 585  | 109  | 60   | 49   | 20 |
| 500  | 500  | 10    | <b>727 700 627</b> | 46.203 | 530  | 620  | 684  | 26   | 585  | 109  | 60   | 49   | 20 |
| 560  | 600  | 10    | <b>727 700 628</b> | 65.823 | 615  | 725  | 796  | 30   | 685  | 118  | 60   | 58   | 20 |
| 630  | 600  | 10    | <b>727 700 629</b> | 67.056 | 642  | 725  | 796  | 30   | 685  | 128  | 60   | 68   | 20 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>