




SYGEF Standard Check valve type 561 silicone free

Without spring

With fusion sockets metric

Model:

- Material: PVDF / silicone free cleaned
- Sealing at a minimum water column of 2 m
- Designed for easy installation and removal
- Vibration free even at high flow velocity
- Flow-optimized return cone, double guided
- For vertical installation
- Compact installation length, same as ball valve type 546
- Z-length, end connectors and union nuts **not** compatible with type 360

Warning: please make sure the diameter is not reduced through welding beads (Danger of turbulences)

d	DN	PN	kv-value	FKM	SP	Weight	D	L	L2	z	closest
(mm)	(mm)	(bar)	($\Delta p=1$ bar)	Code		(kg)	(mm)	(mm)	(mm)	(mm)	inch
			(l/min)								(inch)
16	10	16	190	175 561 211	1	0.160	50	93	56	67	3/8
20	15	16	180	175 561 212	1	0.160	50	95	56	66	1/2
25	20	16	380	175 561 213	1	0.340	58	109	65	77	3/4
32	25	16	460	175 561 214	1	0.360	68	119	71	83	1
40	32	16	850	175 561 215	1	0.670	84	135	85	99	1 1/4
50	40	16	1080	175 561 216	1	0.990	97	147	89	105	1 1/2
63	50	16	1670	175 561 217	1	1.770	124	168	101	117	2
75	65	16	2950	175 561 218	1	3.630	166	235	136	167	2 1/2
90	80	16	3600	175 561 219	1	5.800	200	255	141	180	3
110	100	16	4150	175 561 220	1	9.450	238	305	164	215	4

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>