




Strainer type 305 PVC-U silicone-free
Transparent housing with solvent cement spigots metric

Model:

- Silicone free/paint-compatible
- Overall length EN 558
- With screen PVC-U, perforation $\varnothing$ 0.8 mm

d (mm)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
20	15	10	35	192 305 821	1	0.101	192 305 831	1	0.114
25	20	10	63	192 305 822	1	0.150	192 305 832	1	0.170
32	25	10	85	192 305 823	1	0.255	192 305 833	1	0.229
40	32	10	150	192 305 824	1	0.386	192 305 834	1	0.386
50	40	10	225	192 305 825	1	0.643	192 305 835	1	0.643
63	50	10	346	192 305 826	1	0.979	192 305 836	1	1.033
75	65	10	535	192 305 827	1	1.835	192 305 837	1	1.835
90	80	10	750	192 305 828	1	2.549	192 305 838	1	2.565

d (mm)	D (mm)	H (mm)	L (mm)	L1 (mm)	L2 (mm)	closest inch (inch)
20	43	65	124	130	28	1/2
25	47	76	144	150	37	3/4
32	56	90	154	160	37	1
40	64	104	174	180	44	1 1/4
50	82	124	194	200	48	1 1/2
63	95	148	224	230	60	2
75	106	188	284	290	74	2 1/2
90	120	205	300	310	85	3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>