



Single union safeblock B.S.P. PVC-U
Ball valve with female threaded socket G/male thread R

G	R	PN	EPDM	SP	Weight	A	S	Z	M	L1	L2	L	H
(inch)	(inch)	(bar)	Code		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
3/8	3/8	16	VSA18S160	1	0.096	50	19	53	40	12.0	67	14	53
1/2	1/2	16	VSA18S200	1	0.096	50	19	55	40	15.0	71	16	53
3/4	3/4	16	VSA18S250	1	0.152	59	19	61	45	16.5	80	19	60
1	1	16	VSA18S320	1	0.225	68	21	68	51	19.5	90	22	67
1 1/4	1 1/4	16	VSA18S400	1	0.340	80	25	84	59	21.5	110	26	79
1 1/2	1 1/2	16	VSA18S500	1	0.500	94	27	97	70	21.5	128	31	90
2	2	16	VSA18S630	1	0.845	115	29	119	84	25.5	157	38	107

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>