




ecoFIT Reducer PE100 d25-710mm / SDR11

Model:

- Conventional butt-welding according to DVS 2207
- IR = Infrared-(IR Plus) compatible. Choose fusion parameters: PE100
- * Up to d315 injection moulded, above machined



d	d2	DN	PN	FM	Code	Weight	Lmax	Q1	Q2	s1	s2
(mm)	(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
25	20	20	16	IR	753 908 637	0.008	50	20	18	2.3	1,9
32	20	25	16	IR	753 908 642	0.010	50	20	18	2.9	1,9
32	25	25	16	IR	753 908 641	0.006	50	20	18	2.9	2,3
40	20	32	16	IR	753 908 648	0.017	58	20	20	3.7	1,9
40	25	32	16	IR	753 908 647	0.017	55	20	18	3.7	2,3
40	32	32	16	IR	753 908 646	0.019	55	20	18	3.7	2,9
50	25	40	16	IR	753 908 654	0.025	60	20	18	4.6	2,3
50	32	40	16	IR	753 908 653	0.026	60	20	18	4.6	2,9
50	40	40	16	IR	753 908 652	0.032	60	20	18	4.6	3,7
63	32	50	16	IR	753 908 660	0.046	65	20	18	5.8	2,9
63	40	50	16	IR	753 908 659	0.051	65	20	18	5.8	3,7
63	50	50	16	IR	753 908 658	0.056	65	20	18	5.8	4,6
75	40	65	16	IR	753 908 666	0.070	68	20	20	6.8	3,7
75	50	65	16	IR	753 908 665	0.074	65	20	18	6.8	4,6
75	63	65	16	IR	753 908 664	0.081	65	20	18	6.8	5,8
90	63	80	16	IR	753 908 671	0.125	75	21	17	8.2	5,8
90	75	80	16	IR	753 908 670	0.132	75	22	17	8.2	6,8
110	63	100	16	IR	753 908 672	0.219	90	28	28	10.6	6,2
110	75	100	16	IR	753 908 677	0.219	90	28	17	10.0	6,8
110	90	100	16	IR	753 908 676	0.240	90	28	20	10.0	8,2
125	110	100	16	IR	753 908 680	0.350	100	32	26	11.4	10,0
140	110	125	16	IR	753 908 685	0.437	110	35	28	12.7	10,0
140	125	125	16	IR	753 908 684	0.474	110	35	28	12.7	11,4
160	110	150	16	IR	753 908 690	0.612	120	40	25	14.6	10,0
160	140	150	16	IR	753 908 688	0.674	120	40	33	14.6	12,7
180	90	150	16	IR	753 908 149	0.925	145	50	40	16.4	8,2
180	110	150	16	IR	753 908 150	1.020	150	55	42	16.4	10,0
180	125	150	16	IR	753 908 151	1.020	143	52	40	16.4	11,4
180	140	150	16	IR	753 908 152	1.015	135	51	47	16.4	12,7
180	160	150	16	IR	753 908 153	1.140	135	55	52	16.4	14,6
200	160	200	16	IR	753 908 692	1.247	150	50	35	18.2	14,6
200	180	200	16	IR	753 908 158	1.475	145	62	54	18.2	16,4
225	110	200	16	IR	753 908 695	1.559	171	55	45	20.5	10,0
225	160	200	16	IR	753 908 696	1.590	160	55	37	20.5	14,6
225	180	200	16	IR	753 908 162	1.800	160	64	59	22.7	20,5
225	200	200	16	IR	753 908 697	1.844	160	55	48	20.5	18,2
250	160	250	16	IR	753 908 165	2.305	177	65	53	20.5	14,6
250	180	250	16		753 900 001	2.513	175	60	55	22.7	16,4
250	200	250	16		753 900 002	2.450	190	60	60	22.7	18,2
250	225	250	16		753 908 168	3.025	180	65	65	22.7	20,5
280	200	250	16		753 900 004	3.540	205	70	50	25.4	18,2
280	225	250	16		753 908 172	3.860	210	75	58	25.4	20,5
280	250	250	16		753 908 173	4.155	206	75	60	25.4	22,7
315	200	300	16		753 900 007	3.996	225	80	50	28.6	20,5
315	225	300	16		753 908 176	5.260	237	84	57	28.6	20,5
315	250	300	16		753 908 177	5.415	236	86	64	28.6	22,7
315	280	300	16		753 908 178	5.600	231	86	72	28.6	25,4
*	710	500			753 900 035	20.890	190	84	40	64.5	45,4
*	710	560			753 900 036	19.590	170	81	40	64.5	50,8
*	710	630			753 900 037	17.030	140	71	40	64.5	57,2

Data sheet

valid from: 1/30/24



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>