






DN10/15 - 50



PROGEF Standard
Ball valve type 546
With mounting inserts
With butt fusion spigots SDR17.6 metric

Model:

- Material: PP-H
- For easy installation and removal
- Ball seals PTFE
- Integrated stainless steel mounting inserts
- Valve end and union nut are **not compatible** with type 346 (DN10/15-50) and type 370 (DN65-100)

Option:

- Individual configuration of the valve (see diagram)
- Multifunctional module with integrated limit switches
- Pneumatic or electric actuators from GF

d	DN	PN	kv-value	EPDM	SP	Weight	FKM	SP	Weight
(mm)	(mm)	(bar)	($\Delta p=1$ bar)	Code		(kg)	Code		(kg)
			(l/min)						
50	40	6	1600	167 546 066	1	0.635	167 546 076	1	0.635
63	50	6	3100	167 546 067	1	1.159	167 546 077	1	1.200
75	65	6	5000	167 546 068	1	2.575	167 546 078	1	3.387
90	80	6	7000	167 546 069	1	4.731	167 546 079	1	5.500
110	100	6	11000	167 546 070	1	8.600	167 546 080	1	8.600

d	D	H	H1	H2	L	L1	L2	L4	L5	L6	M	e	closest
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)	inch
													(inch)
50	97	97	51	15	191	128	89	45	54	74	M8	2.9	1 ½
63	124	116	64	15	220	152	101	45	66	87	M8	3.6	2
75	166	149	85	15	266	270	136	70	64	206	M8	4.7	2 ½
90	200	161	105	15	264	270	141	70	64	206	M8	5.5	3
110	238	178	123	22	301	320	164	120	64	256	M12	6.8	4

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 10/3/18



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>