

Ball valve type 542 PVC-U With threaded socket (Rp)




Model:

- For easy installation and removal
- Ball seat PTFE/ red lever

Option:

- Individual configuration of the valve possible
- Assembling of a valve tag possible



d (mm)	DN (mm)	Thread Type	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	EPDM Code	SP	Weight (kg)
16	10	Rp	$\frac{3}{8}$	16	71	161 542 021	1	0.150
20	15	Rp	$\frac{1}{2}$	16	185	161 542 022	1	0.155
25	20	Rp	$\frac{3}{4}$	16	350	161 542 023	1	0.238
32	25	Rp	1	16	700	161 542 024	1	0.348
40	32	Rp	1 $\frac{1}{4}$	16	1000	161 542 025	1	0.603
50	40	Rp	1 $\frac{1}{2}$	16	1600	161 542 026	1	0.800
63	50	Rp	2	16	3100	161 542 027	1	1.575

d (mm)	FKM Code	SP	Weight (kg)	D (mm)	H (mm)	L (mm)	L1 (mm)	L2 (mm)	L5 (mm)	L6 (mm)	z (mm)
16	161 542 031	1	0.150	50	54	95	72	56	26	46	69
20	161 542 032	1	0.155	50	54	100	72	56	26	46	67
25	161 542 033	1	0.238	58	66	115	93	65	34	59	79
32	161 542 034	1	0.348	68	71	128	93	71	34	59	86
40	161 542 035	1	0.603	84	85	146	110	85	41	69	100
50	161 542 036	1	0.800	97	92	152	110	89	41	69	106
63	161 542 037	1	1.575	124	108	177	128	101	49	79	122

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>