Data sheet

valid from: 7/8/23





Adaptor socket PVC-U metric NPT

Model:

- With solvent cement socket metric and NPT (ASTM) taper female thread
- Connection to plastic thread only
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

d (mm)	Thread Type	Size (inch)	PN (bar)	Code	SP	Weight (kg)	z (mm)	L (mm)	s (mm)
20	NPT	½	10	**721 914 206**	10	0.021	5	35	32
25	NPT	¾	10	**721 914 207**	10	0.028	6	40	36
32	NPT	1	10	**721 914 208**	10	0.049	6	45	46
40	NPT	1 ¼	10	**721 914 209**	10	0.076	6	51	55
50	NPT	1 ½	10	**721 914 210**	10	0.110	10	59	65
63	NPT	2	10	**721 914 211**	5	0.175	10	69	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
Phone +41 -(0)52-631 1111
e-mail: info.ps@georgfischer.com
Internet: http://www.gfps.com