



SYGEF Standard adaptor socket female NPT SDR21/PN16

Model:

- Material: PVDF
- With butt fusion spigot and taper female thread NPT
- Avoid stresses when installing and large changes in temperature
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVDF

Note:

* Please keep strictly to the GF internal installation preferences

	d	Size	PN	FM	Thread Type	Code	Weight	L	L1	s	e
	(mm)	(inch)	(bar)				(kg)	(mm)	(mm)	(mm)	(mm)
	20	¾	16	BCF, IR	NPT	735 914 585	0.029	54	30	32	1.9
	20	½	16	BCF, IR	NPT	735 914 586	0.027	54	30	32	1.9
	25	¾	16	BCF, IR	NPT	735 914 587	0.033	58	30	38	1.9
	32	1	16	BCF, IR	NPT	735 914 588	0.066	63	30	48	2.4
	40	1 ¼	16	BCF, IR	NPT	735 914 589	0.085	67	30	58	2.4
	50	1 ½	16	BCF, IR	NPT	735 914 590	0.108	67	30	65	3.0
*	63	2	16	BCF, IR	NPT	735 914 591	0.190	73	30	80	3.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>